

## **AMENDMENT TO THE CLAIMS**

1. (Previously Presented) An apparatus for cache flushing, comprising:  
a list structure to track a status of a plurality of cache entries, wherein  
said list structure is located outside a cache and wherein said list structure does not contain cache  
data or addresses;  
a query mechanism to check said list structure for the state of a cache entry; and  
a cache flush mechanism, logically coupled to said list structure and the cache, to flush a  
cache entry and for modifying said list structure to reflect a flushed state.
2. (Original) An apparatus in accordance with claim 1, wherein:  
said list structure comprises one bit per cache line.
3. (Original) An apparatus in accordance with claim 1, wherein:  
said list structure comprises one bit per plurality of cache lines.
4. (Original) An apparatus in accordance with claim 1, wherein:  
said list structure comprises one bit per cache way.
5. (Previously Presented) An apparatus in accordance with claim 1, further comprising:  
one bit per a variable number of cache lines; and  
wherein a logical arrangement of said list structure conforms to said variable number.

6. (Original) An apparatus in accordance with claim 5, wherein:  
said variable number is set by an operating system.
7. (Previously Presented) An apparatus in accordance with claim 1, wherein:  
a logical arrangement of said list structure matches an architecture of a cache.
8. (Previously Presented) An apparatus in accordance with claim 1, wherein:  
said cache flush mechanism modifies a cache state responsive to results of a query of the  
said list structure.
9. (Original) An apparatus in accordance with claim 8, wherein:  
said cache flush mechanism is logically coupled to a higher level cache for writing back  
modified data.
10. (Original) An apparatus in accordance with claim 8, wherein:  
said cache flush mechanism based on the said list structure is logically coupled to a  
higher level cache for evicting modified data.
11. (Previously Presented) An apparatus in accordance with claim 8, wherein:  
said cache flush mechanism is logically coupled to a main memory for writing back  
modified data.

12. (Previously Presented) An apparatus in accordance with claim 8, wherein:  
said cache flush mechanism is logically coupled to a main memory for evicting modified data.
13. (Original) An apparatus in accordance with claim 1, wherein:  
said list structure is located in random access memory (RAM).
14. (Previously Presented) An apparatus in accordance with claim 1, wherein:  
said list structure is located on a die.
15. (Previously Presented) An apparatus in accordance with claim 1, further comprising:  
a snoop command interpreter to check said list structure in response to a snoop command.
16. (Previously Presented) In a computer system with a cache memory, an apparatus for flushing the cache, comprising:  
a list structure to record modifications to a plurality of cache entries wherein, wherein said list structure is located outside a cache and said list structures does not contain cache data or addresses;  
a cache controller to query said list structure for modifications to said plurality of cache entries and generate a list of cache write-back instructions; and  
wherein said cache controller is to invalidate said plurality of cache entries corresponding to said list of cache write-back instructions.

17. (Original) An apparatus in accordance with claim 16, wherein:  
said list structure is a full list.
18. (Original) An apparatus in accordance with claim 16, wherein:  
said list structure is a partial list.
19. (Previously Presented) An apparatus in accordance with claim 17, wherein:  
said full list comprises one entry per cache line.
20. (Original) An apparatus in accordance with claim 18, wherein:  
said partial list comprises one entry per plurality of cache lines.
21. (Previously Presented) In a multiprocessor computer system with a plurality of processors and cache memory, an apparatus for cache flushing, comprising:
- a list structure to track a status of a plurality of cache entries, wherein said list structure is located outside a cache and wherein said list structure does not contain cache data or addresses;
  - a processor identification within said list structure to link each of said plurality of cache entries to one of the plurality of processors;
  - a query mechanism to check said list structure for a state of a cache entry identified with a processor;
  - a cache flush mechanism to flush a cache entry linked to an identified processor and to modify said list structure to reflect a flushed status.

22. (Original) An apparatus in accordance with claim 21, wherein:  
said list structure contains at least one bit for each cache line.
23. (Original) An apparatus in accordance with claim 21, wherein:  
said list structure contains at least one bit for each of a plurality of cache lines.
24. (Original) An apparatus in accordance with claim 21, wherein:  
said list structure is located on a die with at least one of the plurality of processors.
25. (Previously Presented) A method of flushing a cache, comprising:  
creating a table of cache entries separate from the cache and without the cache data or addresses;  
tracking modified cache entries in said table; and  
generating a write-back command from said table in response to a cache flush event.
26. (Original) A method in accordance with claim 25, further comprising:  
generating an invalidate command in response to a cache flush event.
27. (Previously Presented) A method in accordance with claim 25, further comprising:  
repeating the method for each level of cache.
28. (Original) A method in accordance with claim 25, further comprising:  
querying said table in response to a snoop command.

29. (Original) A method in accordance with claim 25, further comprising writing-back modified cache entries to memory.
30. (Original) A method in accordance with claim 25, further comprising: writing-back modified cache entries to a high level cache.